

2Mega, x3 Zoom IP IR Dome CAMERA

TN-D42031R




제품특징

- 1/2" CMOS Image Sensor
- 지능형 이미지 프리셋 기능
- 최대 줌(Optical x3 / IP x10)
- 최대 60fps@1920x1080
- 쿼드 스트리밍 지원(Pri : H.265/H.264, Sec x3 : H.265/H.264/MJPEG)
- 야간 최대 가시거리 30m 지원
- 지능형 영상분석 기능

*IVA : 가상선/영역, 출입 감지, 배회, 방향 감지, 발생/소멸 감지 등

*분석 이벤트 : 디포커스 감지, 움직임 감지, 템퍼링, 오디오 감지

외관도



Imaging	Sensor	1/2" CMOS Image Sensor
	Zoom	Optical 3x
	Focal length	f = 3.6 ~ 8.0mm
	Angle of view	Horizontal : 98.78°(wide) ~ 44.1°(tele), Vertical : 51.52°(wide) ~ 23.0°(tele)
	Maximum aperture ratio	F1.5
	Min object distance	TBD
	Focus control	Oneshot AF
	Lens type	DC auto iris
	Min illumination	Color : 0.0075 Lux (1/30sec, 35IRE), BW : 0 Lux (IR ON)
	Electronic shutter speed	1/1 ~ 1/100,000 sec
	Day & Night	Day / Night / Auto
	Back light compensation	BLC / HLC / WDR
	White balance	Auto tracing white / Auto white / Manual
	Gain control	Auto
	Noise reduction	Auto / Manual
	Image stabilization	Support
Camera Functions	Defog	Support
	Image rotation	Horizontal(Mirror), Vertical(Flip)
	Motion detection	8 regions on 23x15 cells
	Privacy masking	4 regions
	Video analytics	Motion detection, intrusion detection, line crossing detection, video face detection, camera tampering detection
Video	IR LED	4 pieces, 30m
	Burn-in OSD	Camera title, direction, user-defined Multi-lingual: (English, Korean, French, German, Spanish, Italian, Russian, Japanese, Swedish, Portuguese, Dutch, Hungarian, Finnish, Special Symbols)
	Compression	H.264 / H.265 / MJPEG
	Frame rate	Max 60fps @ 1920x1080
	Bitrate control	H.264/H.265: CBR / VBR / Hybrid MJPEG: VBR
Audio	Resolutions	1920x1080 ~ 352x240
	Streaming	Quad Streaming : Primary: H.264 / H.265, Secondary x 3: H.264 / H.265 / MJPEG
	Compression	G.711 u-law
	Sampling rate	G.711: 8KHz
	Bitrate	G.711: 64Kbps
Event and Alarm	Streaming	Full-duplex
	Input & Output	1 x Line-In (mono), 1 x Line-Out (mono)
	Event sources	Video analytics, Audio detection, Client disconnection, Sensor input, User-defined event
Network	Event actions	E-mail notification, OSD alert, FTP upload, PTZ preset, Alarm control, Recording, HTTP action
	Interface	Ethernet 10/100 base-T (RJ-45)
	Protocol	IPv4/v6, TCP, UDP, IGMP(Multicast), ICMP, DHCP, HTTP, HTTPS, RTP, RTSP, FTP, SNMP, SMTP, UPnP, WS-Discovery, Zero Configuration, NTP, DDNS, RTMP
	Security	Basic/Digest authentication, HTTPS, IP address filtering, User access log, TTA certification
	Application programming interface	Truen protocol/SDK, ONVIF, PSIA, MPEG-TS
Power / Operating Conditions	Power supply	Min DC 12V/2.0A, PoE(Power over Ethernet) : 802.3af
	Power consumption	DC12V/PoE : Max 15W
	Operating condition	-20°C ~ 60°C / Less than 90% RH
	Storage condition	-50°C ~ 60°C / Less than 95% RH
General	Certifications	IP67, IK10, KC
	External devices	1 x Sensor-In (dry contact, NO/NC) 1 x Alarm-Out (dry contact, NO)
	Edge storage	Micro SD/SDHC/SDXC (Max 512GB)
	Color/Material	WHITE / Aluminum
	RAL code	RAL 9003(WHITE)
	Dimension	Ø148 x 123.2mm
	Weight	1.2kg

*상기 스펙은 향후 개발완료시 변경 될 수 있습니다.